

PR - PRA - PRD SERIES Rotary cleaners



METALMONT

HANDLING INNOVATION

PR - PRA - PRD SERIES ROTARY CLEANERS

Reliable performance, construction quality,
easy assembly: the perfect solution

The “PR” rotary cleaner systems are used to pre-clean granular products such as wheat, barley, sunflower, rice, soya, etc. The good product passes through holes of different diameter, chosen according to the product to be treated, while the coarser foreign bodies are removed at the end of the drum. With this type of pre-cleaning it is possible to quickly remove the unwanted coarser parts such as straw, pieces of wood, stones, pieces of corn, etc.

RANGE from 20 to 400 t/h - higher flow rates available on request



MODEL	U.M.	PR-6/2	PR-6/3	PR-6/4	PR-6/5	PR-9/2
Flow rate in wheat pre-cleaning p.s. 0,78 t/m ³ ; RH 20%; impurities 2%	t/h	20	30	40	50	50
Flow rate in corn pre-cleaning p.s. 0,72 t/m ³ ; RH 20%; impurities 2%	t/h	20	30	40	50	46
Flow rate in sunflower pre-cleaning p.s. 0,4 t/m ³ ; RH 16%; impurities 2%	t/h	10	15	20	25	25
Flow rate in soya pre-cleaning p.s. 0,6 t/m ³ ; RH 16%; impurities 2%	t/h	15	23	30	38	38
Flow rate in paddy rice pre-cleaning p.s. 0,6 t/m ³ ; RH 20%; impurities 2%	t/h	15	23	30	38	38
Flow rate in rapeseed pre-cleaning p.s. 0,78 t/m ³ ; RH 16%; impurities 2%	t/h	20	30	40	50	50
Flow rate in barley pre-cleaning p.s. 0,6 t/m ³ ; RH 16%; impurities 2%	t/h	15	23	30	38	38
No. of grids	n	2	3	4	5	2
Drum diameter	mm	630	630	630	630	900
Width of individual grid	mm	650	650	650	650	840
Grid areas	m ²	2,6	3,9	5,1	6,4	4,8
Gearmotor power	kW	0,75	0,75	1,1	1,5	1,5

GENERAL DIMENSIONS

Length	mm	2.420	3.100	3.780	4.460	2.950
Width	mm	800	800	800	800	1.100
Height	mm	1.750	1.800	1.750	1.750	2.065
Height for shipment	mm	1.750	1.800	1.750	1.750	2.095
Inlet flange dimensions	mm	210 x 210	210 x 210	210 x 210	210 x 210	300 x 300
Outlet flange dimensions	mm	190 x 340	190 x 340	190 x 340	190 x 340	340 x 500
Large waste outlet flange dimensions	mm	190 x 340	190 x 340	190 x 340	190 x 340	340 x 430
Height from ground outlet flange	mm	485	485	485	485	485
Product outlet wheelbase distance	mm	670	670	670	670	860
Grid drilling width	mm	570	570	570	570	740
Waste product outlet wheelbase distance	mm	510	510	510	510	525
Vacuum weight (with grids)	kg	310	627	525	650	820

In order to improve the product and for regulatory compliance, the technical specifications, appearance and equipment described in this document may be subject to change without prior notice.

MODEL	U.M.	PR-9/3	PR-9/4	PR-9/5	PR-12/3	PR-12/4
Flow rate in wheat pre-cleaning p.s. 0,78 t/m ³ ; RH 20%; impurities 2%	t/h	75	100	125	120	150
Flow rate in corn pre-cleaning p.s. 0,72 t/m ³ ; RH 20%; impurities 2%	t/h	68	93	111	103	138
Flow rate in sunflower pre-cleaning p.s. 0,4 t/m ³ ; RH 16%; impurities 2%	t/h	35	50	60	60	75
Flow rate in soya pre-cleaning p.s. 0,6 t/m ³ ; RH 16%; impurities 2%	t/h	57	76	96	92	115
Flow rate in paddy rice pre-cleaning p.s. 0,6 t/m ³ ; RH 20%; impurities 2%	t/h	57	76	96	92	115
Flow rate in rapeseed pre-cleaning p.s. 0,78 t/m ³ ; RH 16%; impurities 2%	t/h	75	100	125	120	150
Flow rate in barley pre-cleaning p.s. 0,6 t/m ³ ; RH 16%; impurities 2%	t/h	57	76	96	92	115
No. of grids	n	3	4	5	3	4
Drum diameter	mm	900	900	900	1.200	1.200
Width of individual grid	mm	840	840	840	840	840
Grid areas	m ²	7,1	9,5	11,9	9,5	12,7
Gearmotor power	kW	2,2	3,0	4,0	3,0	4,0

GENERAL DIMENSIONS

Length	mm	3.860	4750	5.650	3.870	4.820
Width	mm	1.100	1.100	1.100	1.400	1.400
Height	mm	2.065	2.065	2.065	2.365	2.365
Height for shipment	mm	2.095	2.095	2.095	2.430	2.430
Inlet flange dimensions	mm	300 x 300	300 x 300	300 x 300	300 x 300	300 x 300
Outlet flange dimensions	mm	340 x 500	340 x 500	340 x 500	340 x 500	340 x 500
Large waste outlet flange dimensions	mm	340 x 500	340 x 500	340 x 500	340 x 500	340 x 500
Height from ground outlet flange	mm	485	485	485	365	365
Product outlet wheelbase distance	mm	860	860	860	860	860
Grid drilling width	mm	740	740	740	740	740
Waste product outlet wheelbase distance	mm	560	560	560	560	560
Vacuum weight (with grids)	kg	970	1.130	1.285	1.280	1.540

In order to improve the product and for regulatory compliance, the technical specifications, appearance and equipment described in this document may be subject to change without prior notice.

MODEL	U.M.	PR-12/5	PR-16/3	PR-16/4	PR-16/5
Flow rate in wheat pre-cleaning p.s. 0,78 t/m ³ ; RH 20%; impurities 2%	t/h	200	240	320	400
Flow rate in corn pre-cleaning p.s. 0,72 t/m ³ ; RH 20%; impurities 2%	t/h	182	220	300	370
Flow rate in sunflower pre-cleaning p.s. 0,4 t/m ³ ; RH 16%; impurities 2%	t/h	100	120	160	205
Flow rate in soya pre-cleaning p.s. 0,6 t/m ³ ; RH 16%; impurities 2%	t/h	153	180	246	307
Flow rate in paddy rice pre-cleaning p.s. 0,6 t/m ³ ; RH 20%; impurities 2%	t/h	153	180	246	307
Flow rate in rapeseed pre-cleaning p.s. 0,78 t/m ³ ; RH 16%; impurities 2%	t/h	200	240	320	400
Flow rate in barley pre-cleaning p.s. 0,6 t/m ³ ; RH 16%; impurities 2%	t/h	153	180	246	307
No. of grids	n	5	3	4	5
Drum diameter	mm	1.200	1.600	1.600	1.600
Width of individual grid	mm	840	950	950	950
Grid areas	m ²	15,8	14,3	19,1	23,9
Gearmotor power	kW	5,5	5,5	7,5	11,0

GENERAL DIMENSIONS

Length	mm	5.720	4.680	5.680	6.680
Width	mm	1.400	2.095	2.095	2.095
Height	mm	2.365	2.200	2.200	2.200
Height for shipment	mm	2.430	2.240	2.240	2.240
Inlet flange dimensions	mm	300 x 300	400 x 400	400 x 400	400 x 400
Outlet flange dimensions	mm	340 x 500	350 x 350	350 x 350	350 x 350
Large waste outlet flange dimensions	mm	340 x 500	350 x 350	350 x 350	350 x 350
Height from ground outlet flange	mm	365	90	90	90
Product outlet wheelbase distance	mm	860	1.000	1.000	1.000
Grid drilling width	mm	740	880	880	880
Waste product outlet wheelbase distance	mm	560	650	650	650
Vacuum weight (with grids)	kg	1.910	2.100	2.450	2.800

In order to improve the product and for regulatory compliance, the technical specifications, appearance and equipment described in this document may be subject to change without prior notice.

PRA SERIES

The PRA rotary cleaner is the combined solution consisting of a PR Series rotary cleaner and a Metalmont PA Series suction cleaner. In this configuration, the machine can efficiently and accurately clean and sort the product with a significant reduction of dust emissions into the atmosphere.

RANGE from 50 to 150 t/h - higher flow rates available on request



MODEL	U.M.	PRA-9/3	PRA-9/4	PRA-9/5
Flow rate in wheat pre-cleaning 14% RH*	t/h	50	70	90
Flow rate in corn pre-cleaning 14% RH*	t/h	45	60	80
Flow rate in sunflower pre-cleaning 12% RH*	t/h	25	35	45
Flow rate in soya pre-cleaning 12% RH*	t/h	35	50	65
Flow rate in paddy rice pre-cleaning 12% RH*	t/h	35	50	65
Flow rate in rapeseed pre-cleaning 12% RH*	t/h	50	70	90
Flow rate in barley pre-cleaning 12% RH*	t/h	35	50	65
No. of grids	n	3	4	5
Drum diameter	mm	900	900	900
Grid areas	m ²	7,1	9,5	11,9
Drum motor installed power	kW	2,2	3,0	4,0
Type of ignition recommended for the motor		soft start	soft start	soft start
Suction fan power	kW	3,0	4,0	5,5
Suction fan flow rate	m ³ /h	3.600	4.320	6.500

GENERAL DIMENSIONS

Length	mm	4.560	5.460	6.350
Width	mm	1.100	1.100	1.100
Height	mm	3.500	3.500	3.600
Max height for shipment	mm	2.095	2.095	2.095
Inlet flange dimensions	mm	300 x 300	300 x 300	300 x 300
Outlet flange dimensions	mm	340 x 500	340 x 500	340 x 500
Height from ground outlet flange	mm	485	485	365
Product outlet wheelbase distance	mm	860	860	860
Grid drilling width	mm	740	740	740
Waste product outlet wheelbase distance	mm	560	560	560
Vacuum weight (with grids)	kg	970	1.130	1.270

In order to improve the product and for regulatory compliance, the technical specifications, appearance and equipment described in this document may be subject to change without prior notice.

MODEL	U.M.	PRA-12/3	PRA-12/4	PRA-12/5
Flow rate in wheat pre-cleaning 14% RH*	t/h	100	120	150
Flow rate in corn pre-cleaning 14% RH*	t/h	90	110	135
Flow rate in sunflower pre-cleaning 12% RH*	t/h	50	60	75
Flow rate in soya pre-cleaning 12% RH*	t/h	75	90	115
Flow rate in paddy rice pre-cleaning 12% RH*	t/h	75	90	115
Flow rate in rapeseed pre-cleaning 12% RH*	t/h	100	120	150
Flow rate in barley pre-cleaning 12% RH*	t/h	75	90	115
No. of grids	n	3	4	5
Drum diameter	mm	1.200	1.200	1.200
Grid areas	m ²	9,5	12,7	15,8
Drum motor installed power	kW	3,0	4,0	5,5
Type of ignition recommended for the motor		soft start	soft start	soft start
Suction fan power	kW	7,5	7,5	11,0
Suction fan flow rate	m ³ /h	7.500	7.500	10.800

GENERAL DIMENSIONS

Length	mm	4.570	5.520	5.720
Width	mm	1.400	1.400	1.400
Height	mm	3.800	3.800	3.800
Max height for shipment	mm	2.430	2.430	2.430
Inlet flange dimensions	mm	300 x 300	300 x 300	300 x 300
Outlet flange dimensions	mm	340 x 500	340 x 500	340 x 500
Height from ground outlet flange	mm	365	365	365
Product outlet wheelbase distance	mm	860	860	860
Grid drilling width	mm	740	740	740
Waste product outlet wheelbase distance	mm	560	560	560
Vacuum weight (with grids)	kg	1.280	1.540	1.910

In order to improve the product and for regulatory compliance, the technical specifications, appearance and equipment described in this document may be subject to change without prior notice.

PRD SERIES

The PRD series rotary cleaner is the combined solution consisting of a PR Series rotary cleaner and a Metalmont PD Series suction cleaner. In this configuration, the machine can efficiently and accurately clean and sort the product with a significant reduction of dust emissions into the atmosphere.

RANGE from 50 to 300 t/h - higher flow rates available on request



In order to improve the product and for regulatory compliance, the technical specifications, appearance and equipment described in this document may be subject to change without prior notice.

MODEL	U.M.	PRD-9/3	PRD-9/4	PRD-9/5	PRD-12/3
Flow rate in wheat cleaning p.s. 0,78 t/m ³ ; RH 14%; impurities 2%	t/h	50	70	90	100
Flow rate in corn cleaning p.s. 0,72 t/m ³ ; RH 14%; impurities 2%	t/h	45	60	80	90
Flow rate in sunflower cleaning p.s. 0,4 t/m ³ ; RH 12%; impurities 2%	t/h	25	35	45	50
Flow rate in soya cleaning p.s. 0,6 t/m ³ ; RH 12%; impurities 2%	t/h	35	50	65	75
Flow rate in paddy rice cleaning p.s. 0,6 t/m ³ ; RH 12%; impurities 2%	t/h	35	50	65	75
Flow rate in rapeseed cleaning p.s. 0,78 t/m ³ ; RH 12%; impurities 2%	t/h	50	70	90	100
Flow rate in barley cleaning p.s. 0,6 t/m ³ ; RH 12%; impurities 2%	t/h	35	50	65	75
No. of grids	n	3	4	5	3
Drum diameter	mm	900	900	900	1200
Grid areas	m ²	7,1	9,5	11,9	9,5
Drum motor installed power	kW	2,2	3,0	4,0	3,0
Type of ignition recommended for the motor		soft start	soft start	soft start	soft start
Suction fan power	kW	3,0	4,0	5,5	7,5
Suction fan flow rate	m ³ /h	3.600	4.320	6.500	7.500
Inlet product distribution roller power	kW	0,18	0,18	0,18	0,37
Waste screw power	kW	0,18	0,18	0,18	0,37
GENERAL DIMENSIONS					
Length	mm	3910	4.770	5.630	3.900
Width	mm	1.500	1.500	1.500	1.800
Height	mm	3.600	3.600	3.600	4.000*
Max height for shipment	mm	2.095	2.095	2.095	2.430*
Inlet flange dimensions	mm	300 x 300	300 x 300	300 x 300	300 x 300
Outlet flange dimensions	mm	340 x 500	340 x 500	340 x 500	340 x 500
Large waste outlet flange dimensions	mm	340 x 500	340 x 500	340 x 500	340 x 500
Height from ground outlet flange	mm	485	485	485	365*
Product outlet wheelbase distance	mm	860	860	860	860
Grid drilling width	mm	740	740	740	740
Waste product outlet wheelbase distance	mm	560	560	560	560
Vacuum weight (with grids)	kg	1.720	1.880	2.080	2.160

In order to improve the product and for regulatory compliance, the technical specifications, appearance and equipment described in this document may be subject to change without prior notice.

MODEL	U.M.	PRD-12/4	PRD-12/5	PRD-16/4	PRD-16/5
Flow rate in wheat cleaning p.s. 0,78 t/m ³ ; RH 14%; impurities 2%	t/h	125	170	220	300
Flow rate in corn cleaning p.s. 0,72 t/m ³ ; RH 14%; impurities 2%	t/h	115	155	200	275
Flow rate in sunflower cleaning p.s. 0,4 t/m ³ ; RH 12%; impurities 2%	t/h	60	85	110	150
Flow rate in soya cleaning p.s. 0,6 t/m ³ ; RH 12%; impurities 2%	t/h	95	130	165	230
Flow rate in paddy rice cleaning p.s. 0,6 t/m ³ ; RH 12%; impurities 2%	t/h	95	130	165	230
Flow rate in rapeseed cleaning p.s. 0,78 t/m ³ ; RH 12%; impurities 2%	t/h	125	170	220	300
Flow rate in barley cleaning p.s. 0,6 t/m ³ ; RH 12%; impurities 2%	t/h	95	130	165	230
No. of grids	n	4	5	4	5
Drum diameter	mm	1.200	1.200	1.600	1.600
Grid areas	m ²	12,7	15,8	19,1	23,9
Drum motor installed power	kW	4,0	5,5	7,5	9,2
Type of ignition recommended for the motor		soft start	soft start	soft start	soft start
Suction fan power	kW	7,5	11,0	15,0	15,0 - 18,5
Suction fan flow rate	m ³ /h	7.500	10.080	10.080	14.400
Inlet product distribution roller power	kW	0,37	0,37	0,37	0,75
Waste screw power	kW	0,37	0,37	0,37	0,37
GENERAL DIMENSIONS					
Length	mm	4.800	5.700	5.800	6.800
Width	mm	1.800	1.800	2.400	2.400
Height	mm	4.000*	4.000*	3.800	3.800
Max height for shipment	mm	2.430*	2.430*	2.240	2.240
Inlet flange dimensions	mm	300 x 300	300 x 300	400 x 400	400 x 400
Outlet flange dimensions	mm	340 x 500	340 x 500	350 x 350	350 x 350
Large waste outlet flange dimensions	mm	340 x 500	340 x 500	350 x 350	350 x 350
Height from ground outlet flange	mm	365*	365*	90	90
Product outlet wheelbase distance	mm	860	860	1.000	1.000
Grid drilling width	mm	740	740	880	880
Waste product outlet wheelbase distance	mm	560	560	650	650
Vacuum weight (with grids)	kg	2.420	2.800	3.450	3.800

In order to improve the product and for regulatory compliance, the technical specifications, appearance and equipment described in this document may be subject to change without prior notice.

ACCESSORIES AND DEVICES

Series of internal product distribution blades	●	●	●	●	●	●	●	●	●	●
Manually-operated deflector under the last grid	●	●	●	●	●	●	●	●	●	●
A series of grids supplied with the machine	●	●	●	●	●	●	●	●	●	●
PVC cleaning brushes mounted on the machine	●	●	●	●	●	●	●	●	●	●
Waste conveying spiral (on PD Series cleaner)	●	●	●	●	●	●	●	●	●	●
Visual inspection porthole on the grid access door	●	●	●	●	●	●	●	●	●	●
Visual inspection porthole on the PD Series cleaner	●	●	●	●	●	●	●	●	●	●
Hole for suction on PD Series cleaner (diameter)	mm	●/200	●/200	●/200	●/200	●/200	●/200	●/200	●/250	●/250
Manual drum inclination variator	●	●	●	●	●	●	●	●	●	●
Limit switch motorised drum inclination variator	○	○	○	○	○	○	○	○	○	○
Series of dry beech rollers with support weight	○	○	○	○	○	○	○	○	○	○
Machine in ATEX 22 execution	○	○	○	○	○	○	○	○	○	○
Electrical control panel (on cleaner)	○	○	○	○	○	○	○	○	○	○
Manual inlet by-pass	○	○	○	○	○	○	○	○	○	○
Manual inlet by-pass with limit switch	○	○	○	○	○	○	○	○	○	○
Inductive limit switch motorised inlet by-pass	○	○	○	○	○	○	○	○	○	○
Good product collection hopper for 2 grids	○	○	○	○	○	○	○	○	○	○
Good product collection hopper for 3 grids	○	○	○	○	○	○	○	○	○	○
Good product collection hopper for 4 grids	○	○	○	○	○	○	○	○	○	○
Coarse waste collection hopper (diameter)	mm	○/250	○/250	○/250	○/250	○/250	○/250	○/250	○/300	○/300
10 mm thick PE1000 polyethylene slide coatings	○	○	○	○	○	○	○	○	○	○
Cleaner grid holder frame	○	○	○	○	○	○	○	○	○	○
Walkway and cleaner extension (configurations according to system)	○	○	○	○	○	○	○	○	NA	NA

● - Standard

○ - Optional

NA - Not available



METALMONT

HANDLING INNOVATION

Metalmont s.r.l.
Via Guglielmo Marconi, 92
31020 Revine Lago (TV) Italy
☎ +39 0438 562028
✉ info@metalmont.it

METALMONT.IT